



## SL422H32G0 - FriFri Super Easy 422 Electric Free-standing Twin Tank Fryer with Filtration - 2 Baskets - W 400 mm - 2 x 11.0 kW

When budget is a primary consideration, FriFri's unrivalled credentials, know-how and quality are still well within your reach. A free standing Super Easy 422 offers outstanding value with no compromise in quality or performance.

- ✓ Outstanding quality with no compromise in quality or performance.
- ✓ Mechanical thermostat maintains oil to within +/-8 °C of the temperature selected.
- ✓ Low watts density element with a large surface area in contact with the oil for fast recovery time and to prevent scorching which degrades oil.
- ✓ Keeping your oil in peak condition! Integral gravity filtration extends oil life by up to 75% saving you money on oil purchase and disposal costs. Optional xFri© filters the oil at the push of a button and returns oil to the tank. Filter the oil safely, even while it's still hot, mid service if necessary, and resume frying in minutes – so easy there is no excuse not to!
- ✓ Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.
- ✓ Optimum Allergy Control. Supplied with separate oil buckets, and can be supplied with separate pumped filtration systems, providing completely segregated gravity filtration for optimum allergen control or to cater for dietary preferences.

### Specifications

Summary		Power and Performance	
<b>Brand</b>	FriFri	<b>Total Power kW</b>	2 x 11.0
<b>Range</b>	Super Easy	<b>Temperature Range °C</b>	95-190
<b>Power Type</b>	Electric	<b>IP Rating</b>	IPX4
<b>Unit Type</b>	Free-standing	<b>Temperature Control</b>	Mechanical
<b>Available in UK Only</b>	No		
<b>UK Warranty</b>	2 Years Parts and Labour Warranty		
<b>Export Warranty</b>	Contact your local dealer		
<b>GTIN</b>	5056105122753		

Key Specifications		Capacity	
<b>Number of Baskets</b>	2	<b>Product Output per Hour</b>	2 x 20kg fries - 7mm [frozen]
<b>Number of Tanks</b>	2	<b>Capacity Litres</b>	2 x 7.5-9.0
<b>Gravity Filtration</b>	Yes		
<b>Pumped Filtration</b>	No		
<b>Drain Location</b>	Through the body		

## Weights and Dimensions

Unit Height (External) mm	986
Unit Width (External) mm	397.5
Unit Depth (External) mm	650
Net Weight Kg	56

## Supply Connections

Requires Installation	Yes
Requires Electrical Supply	Yes
UK 3 Pin Plug	No
Requires Hardwiring	Yes
Electrical Supply Rating Watts	2 x 11,000
Three Phase Amps	L1=2 x 15.9; L2=2 x 15.9; L3=2 x 15.9
Three Phase Voltage	400
Number of Supply Cables	2

## Shipping

Packed Weight Kg	59.95
Packed Height cm	113
Packed Width cm	79
Packed Depth cm	52

## Available Options

## Oil Pump

OP1	1 Oil Pump
OP2	2 Oil Pumps

## Legs/Castors

OC200	OC200 - 2 Castors [Fixed at Rear] + 2 Legs [at Front]
OC400	OC400 - 4 Castors [2 Fixed at Rear + 2 Swivel at Front]



## Lincat Limited

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

Company No: 2175448

A member company of



## Customer Care

Tel: +44 1522 875500  
Email: care@lincat.co.uk

## Export Customers

Tel: +44 1522 875536  
Email: export@lincat.co.uk

## Opening Hours

Monday – Friday:  
8.30am – 5pm