



SD422L32G0 - FriFri Super Easy 422 Electric Drop-in Twin Tank Fryer with Filtration - 2 Baskets - W 400 mm - 2 x 7.5 kW

When budget is a primary consideration, FriFri's unrivalled credentials, know-how and quality are still well within your reach. A drop in Super Easy 422 offers outstanding value with no compromise in quality or performance.

- ✔ Outstanding quality with no compromise in quality or performance.
- ✔ Mechanical thermostat maintains oil to within +/-8 °C of the temperature selected.
- ✔ Low watts density element with a large surface area in contact with the oil for fast recovery time and to prevent scorching which degrades oil.
- ✔ Keeping your oil in peak condition! Integral gravity filtration extends oil life by up to 75% saving you money on oil purchase and disposal costs. Optional xFri© filters the oil at the push of a button and returns oil to the tank. Filter the oil safely, even while it's still hot, mid service if necessary, and resume frying in minutes – so easy there is no excuse not to!
- ✔ Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.
- ✔ Optimum Allergy Control. Supplied with separate oil buckets, and can be supplied with separate pumped filtration systems, providing completely segregated gravity filtration for optimum allergen control or to cater for dietary preferences.

Specifications

Summary

| | |
|-----------------------------|-----------------------------------|
| Brand | FriFri |
| Range | Super Easy |
| Power Type | Electric |
| Unit Type | Drop in |
| Available in UK Only | No |
| UK Warranty | 2 Years Parts and Labour Warranty |
| Export Warranty | Contact your local dealer |
| GTIN | 5056105123620 |

Power and Performance

| | |
|-----------------------------|------------|
| Total Power kW | 2 x 7.5 |
| Temperature Range °C | 95-190 |
| IP Rating | IPX4 |
| Temperature Control | Mechanical |

Key Specifications

| | |
|---------------------------|------------------|
| Number of Baskets | 2 |
| Number of Tanks | 2 |
| Gravity Filtration | Yes |
| Pumped Filtration | No |
| Drain Location | Through the body |

Capacity

| | |
|--------------------------------|-------------------------------|
| Product Output per Hour | 2 x 17kg fries - 7mm [frozen] |
| Capacity Litres | 2 x 7.5-9.0 |

Weights and Dimensions

| | |
|---------------------------|-------|
| Unit Height (External) mm | 849 |
| Unit Width (External) mm | 397.5 |
| Unit Depth (External) mm | 630 |
| Net Weight Kg | 32 |

Supply Connections

| | |
|--------------------------------|---------------------------------------|
| Requires Installation | Yes |
| Requires Electrical Supply | Yes |
| UK 3 Pin Plug | No |
| Requires Hardwiring | Yes |
| Electrical Supply Rating Watts | 2 x 7,500 |
| Three Phase Amps | L1=2 x 10.9; L2=2 x 10.9; L3=2 x 10.9 |
| Three Phase Voltage | 400 |
| Number of Supply Cables | 2 |

Shipping

| | |
|------------------|------|
| Packed Weight Kg | 35.2 |
| Packed Height cm | 72 |
| Packed Width cm | 89 |
| Packed Depth cm | 80 |

Available Options

Oil Pump

| | |
|-----|-------------|
| OP1 | 1 Oil Pump |
| OP2 | 2 Oil Pumps |



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm